

External Gear Pump Alu - Group 3 - Counterclockwise Tapered Shaft 1:8 - BSP Threaded Ports






- **Series :** BTD
- **Group :** 3
- **Rotation :** Counter-clockwise (Left-hand)
- **Displacements :** 22 / 26 / 28 / 32 / 36 / 42 / 46 / 50 / 55 cm³/rev (cc/rev)
- **Suction port :** 3/4" or 1" BSP female depending on displacement
- **Pressure port :** 3/4" BSP female
- **Maximum pressure :** 200 bar
- **Flange and cover :** Cast iron
- **Brand :** Trale







Selection Table : External Gear Pump Alu - Group 3 - Counterclockwise - Tapered Shaft 1:8 - BSP Threaded Ports

Code SEDIAP	Référence Dicsa	R1	R2	Press. max. (bar)	Limite press. (bar)	TR./MN.	cm³/ rev.	A	B
PR#AA195	BTD3220I01	3/4" BSP	3/4" BSP	200	250	3000	22 CC	130,5	63,5
PR#AA196	BTD3260I01	3/4" BSP	3/4" BSP	200	250	3000	26 CC	133,5	65
PR#AA197	BTD3280I01	1" BSP	3/4" BSP	200	250	3000	28 CC	134,5	65,5
PR#AA198	BTD3320I01	1" BSP	3/4" BSP	200	250	3000	32 CC	137,5	67
PR#AA199	BTD3360I01	1" BSP	3/4" BSP	200	250	3000	36 CC	140,5	68,5
PR#AA200	BTD3420I01	1" BSP	3/4" BSP	200	250	2800	42 CC	144,5	70,5
PR#AA201	BTD3460I01	1" BSP	3/4" BSP	200	250	2400	46 CC	147,5	72
PR#AA202	BTD3500I01	1" BSP	3/4" BSP	200	250	2400	50 CC	150	73,5
PR#AA203	BTD3550I01	1" BSP	3/4" BSP	200	250	2400	55 CC	153,5	75